

1 **CLAIMS:**

2
3 What is claimed is:

- 4
- 5 1. A lighting device, comprising:
- 6 a display element that is removably attached to a support element by an attaching
- 7 means;
- 8 a light bulb being positioned on said support element such that said light bulb
- 9 illuminates said display element;
- 10 an electrical power source stored within said support element; and
- 11 said support element being removably affixed to a surface.
- 12
- 13 2. The device of claim 1, wherein said display element has a top region that is
- 14 aesthetically designed and a bottom region that attaches to a top end of said support element
- 15 via an attaching means.
- 16
- 17 3. The device of claim 2, wherein said bottom region of said display element is
- 18 substantially annular and accommodates the top end of the support element in a frictional
- 19 manner.
- 20
- 21 4. The device of claim 2, wherein said bottom region of said display element has a
- 22 substantially annular wall;
- 23 said attaching means being defined by at least an aperture defined through said wall
- 24 and able to receive a retractable protruding member extending from said support element;
- 25 whereby, the protruding member extends through said aperture by force from a

1 resilient member in a resting stage and prevents removal of said display element.

2

3 5. The device of claim 2, wherein said light bulb is positioned on said top end of said
4 support element;

5 a bottom end of said support element being distal to said top end;

6 said support element being tubular in nature such that said bottom end has an opening
7 for frictionally receiving an affixing element therein.

8

9 6. The device of claim 5, wherein the affixing element is telescopic in nature,
10 whereby said display element may be presented at differing heights.

11

12 7. The device of claim 2, wherein said light bulb is positioned on said top end of said
13 support element;

14 a bottom end of said support element being distal to said top end;

15 said support element being tubular in nature such that said bottom end has an opening
16 for frictionally receiving an upper end of an extending element therein;

17 said extending element having an lower end that is distal to said upper end;

18 said extending element being tubular in nature such that said lower end receives a top
19 boundary of an affixing element therein in a frictional manner;

20 an affixing end of said affixing element being distal to said top boundary and
21 removably attaching to a surface.

22

23 8. The device of claim 7, wherein the extending element and said affixing element
24 are telescopic in nature, whereby said display element may be presented at differing heights.

25

1 9. The device of claim 2, wherein said power source is a rechargeable battery that is
2 recharged by a solar cell that is affixed to an outer wall of said support element and is in
3 communication with said rechargeable battery therethrough.
4

5 10. The device of claim 8, wherein said power source is a rechargeable battery that is
6 recharged by a solar cell that is affixed to an outer wall of said support element and is in
7 communication with said rechargeable battery therethrough.
8

9 11. An adaptable lighting device, comprising:

10 a display element having a top region of an aesthetic design and a bottom region
11 having a hole therein;

12 a support element having a top end and a bottom end and said top end being insertable
13 into said hole of said bottom region of said display element in a frictional manner to
14 removably engage said bottom region via an attaching means;

15 a light bulb being positioned on said top end of said support element such that said
16 light bulb illuminates said display element;

17 an electrical power source stored within said support element; and
18 said support element being removably affixed to a surface.
19

20 12. The device of claim 11, wherein said bottom region of said display element has a
21 substantially annular wall;

22 said attaching means being defined by at least an aperture defined through said wall
23 and able to receive a retractable protruding member extending from said support element;

24 whereby, the protruding member extends through said aperture by a force exerted by a
25 resilient member in a resting stage and prevents removal of said display element.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

13. The device of claim 11, wherein said light bulb is positioned on said top end of
said support element;
said support element being tubular in nature such that said bottom end has an opening
for frictionally receiving an affixing element therein;
said affixing element being telescopic in nature, whereby said display element may be
presented at differing heights.

14. The device of claim 11, wherein said light bulb is positioned on said top end of
said support element;
said support element being tubular in nature such that said bottom end has an opening
for frictionally receiving an upper end of an extending element therein;
said extending element have a lower end that is distal to said upper end;
said extending element being tubular in nature such that said lower end receives a top
boundary of an affixing element therein in a frictional manner;
an affixing end of said affixing element being distal to said top boundary and
removably attaching to a surface; and
said extending element and said affixing element are telescopic in nature, whereby
said display element may be presented at differing heights.

15. The device of claim 14, wherein said power source is a rechargeable battery that
is recharged by a solar cell that is affixed to an outer wall of said support element and is in
communication with said rechargeable battery therethrough.

16. The device of claim 14, wherein said display element is manufactured from a

1 translucent polymeric compound.

2

3 17. The device of claim 16, wherein said translucent polymeric compound is selected
4 from a group consisting of polystyrene and polyethylene.

5

6 18. The device of claim 11, wherein said power source is obtained from
7 commercially available electricity wired thereto.

8

9 19. The device of claim 14, wherein said affixing element, said extending element,
10 and said support element are manufactured to be impenetrable to liquids.

11

12 20. A portable lighting device, comprising:

13 a display element having a top region of an aesthetic design and a bottom region
14 having defined by an annular wall such that a hole is defined therein;

15 a support element having a top end and a bottom end and said top end being insertable
16 into said hole of said bottom region of said display element in a frictional manner to
17 removably engage said bottom region via an attaching means;

18 said attaching means being defined by at least an aperture defined through said wall
19 and able to receive a retractable protruding member extending from said support element and,
20 whereby, the protruding member extends through said aperture by a force exerted by a
21 resilient member in a resting stage and prevents removal of said display element

22 a light bulb being positioned on said top end of said support element such that said
23 light bulb illuminates said display element;

24 an electrical power source stored within said support element;

25 said support element being tubular in nature such that said bottom end has an opening

1 for frictionally receiving an upper end of an extending element therein;
2 said extending element having a lower end that is distal to said upper end;
3 said extending element being tubular in nature such that said lower end receives a top
4 boundary of an affixing element therein in a frictional manner;
5 an affixing end of said affixing element being distal to said top boundary and
6 removably attaching to a surface; and
7 said extending element and said affixing element are telescopic in nature, whereby
8 said display element may be presented at differing heights.
9

10065749.022602